


\*\* NOTE : Not all approvals are available on all models. Please request a certified drawing if specific approvals are required.

**DIMENSIONS**

<b>RATED CAPACITY</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>	<b>G</b>	<b>H</b>	<b>J</b>	<b>K</b>	<b>L</b>	<b>M</b>
<b>lb/inches</b>												
1500-2500	9.00	6.00	.62	1.75	.59	.53	.69	.56	5/8-18UNF	.31	1.19	1.13
5000	10.00	6.25	.75	2.00	.84	.78	.94	.50	7/8-14UNF	.50	1.44	1.44
<b>kg/mm</b>												
680.4-1134.0	228.6	152.4	15.8	44.5	14.9	13.5	17.5	14.2	5/8-18UNF	7.9	30.2	28.7
2268.0	254.0	158.8	19.1	50.8	21.3	19.8	23.9	12.7	7/8-14UNF	12.7	36.6	36.6

**SPECIFICATIONS**

<b>Rated Capacity</b>	lb	1K;2K;5K;10K
<b>Full Scale Output</b>	mV/V	2.0
<b>Non-linearity</b>	%	<±0.03
<b>Hysteresis Error</b>	%	<±0.02
<b>Bridge Resistance</b>	Ω	1000
<b>Rated Excitation</b>	V(DC/AC)	10 (15V Maximum)
<b>Insulation Resistance</b>	GΩ	5
<b>Nominal Temperature Range</b>	°C/°F	-18 to 65 / 0 to 150
<b>Safe Overload</b>	% of full scale	150
<b>Safe Sideload</b>	% of full scale	100
<b>Seal Type</b>		Environmentally Sealed
<b>Cable Length</b>	m	15' / 4.6



- Exc+ Green
- Sig+ White
- Exc- Black
- Sig- Red
- Shield Bare

**INTERCHANGEABLE PRODUCTS**

<b>Manufacturer</b>	<b>Model</b>
Fairbanks.....	3-53581-X, 3-529921-1